

ORDER TECHNICAL REVIEW

06.08.2020

Customer name	UNITEC-D High-Tech-Industrieprodukte-Vertriebs GmbH	Order confirmation	SOG029553-2
Customer PO	56255 - 4432	Line no.	2
Requested ship date	01.08.2020	Commercial validation date	
Quantity	4,00	Confirmed ship date	01.09.2020
		Order seized by:	Ines LINNERBAUER
		Item name	AQ0025-30sek-220-230VAC-

SERVICE CONDITIONS

SERVICE CONDITIONS	Required torque O (Nm) ... : 250	Stem diam. (mm) : 0,00	
	Required torque C (Nm) ... : 250	VALVE Lead (mm) : 0,00	
	Number of turns in output : 0,25	Lift (mm) : 0,00	
	Closing direction : Clockwise		
	Customer specifications :		
	Observation :		

ACTUATOR

Actuator : AQ25	Actuator's speed (Rpm) : 0,50
-----------------------	-------------------------------------

MECHANICAL SPECIFICATIONS

Protection : _NotExplosionProof IP68	Output flange : F07/F10
Box type : Standard	Output form : N/A
Class : III	Machining type : unmachined
Output speed (RPM) : 0,50	Manual command : Declutchable Ø 125 mm
Operating time (s) : 30	Paint : BCPS-C3-01
Max torque (Nm) : 250 Permanent (Nm): 125	Painting process : Intermediate Corrosi
Torque set O (Nm) : 250	Color : ELFENBEIN=RAL1014
Torque set C (Nm) : 250	
Temperature : Standard -20°C to 60°C	

MOTOR SPECIFICATIONS

Motor : Electric 1Ph 230V 50Hz	Motor duty (%) : S4 - 50
Power (kW) : 0,04	Nominal intensity (A) : 1,10 Starting current (A) : 1,40

ELECTRICAL SPECIFICATIONS

Control type : Switch prewired	Wiring diagram : WD_500097_FREN
Options (incl.) : Analog Positioner (Input + Output Signals)	
End of travel limit switches : Opening : 2 & Closing : 2 - Type : SPDT	
Torque limit switches qty : Opening : 1 & Closing : 1 - Type :	
Customer's connection : Plug plastic 2xM20 ISO	
Heater : 230 V	

PARTICULAR SPECIFICATIONS

Quality level : Q3	Quality plan :	Dimensional drawing ... : CD_01502 Ver. C
Electronic card's configura: Standard		Orientations :